

ng-open DIRECTIVE IN ANGULARJS

- The **ng-open directive** in AngularJS specifies the open attribute of a list.
- It is used to sets the open attribute of a details list.
- ng-open directive supported by the **<detail>** element.
- Whenever the expression inside the **ng-open** attribute returns true value, then the details list will be visible.
- When we use interpolation inside open then we need special directive to utilize.
- Following browsers like Edge, Firefox, and Internet Explorer will not support, so instead use ngShow or ngHide.

Syntax for ng-open Directive in AngularJS:

```
<details ng-open="expression">.....</details>
```

Parameter Values:

Parameter	Type	Description
ng-open	string	If the expression returns true value, then the special attribute "open" will be set on the element.

Sample code for ng-open Directive in AngularJS:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy AngularJS Tutorial</title>
    <script
src="https://ajax.googleapis.com/ajax/libs/angularjs/1.5.6/angular.min.js">
      </script>
  </head>
  <body ng-app="">
    <h3>ng-open Directive in AngularJS Tutorial</h3>
    Click Here:<input type="checkbox" ng-model="detail"><br><br>
    <details ng-open="detail">
      <summary>Show the Tutorial List</summary>
      <p>HTML</p>
      <p>CSS</p>
      <p>AngularJS</p>
      <p>PHP</p>
    </details>
  </body>
</html>
```



ng-open Directive using in AngularJS:

```
<details ng-open="detail">
  <summary>Show the Tutorial List</summary>
  <p>HTML</p>
  <p>CSS</p>
  <p>AngularJS</p>
  <p>PHP</p>
</details>
```

- The ng-open directive used to set the open attribute of a details list.



Code Explanation for ng-open Directive in AngularJS:


```

<!DOCTYPE html>
<html>
    <head>
        <title>Wikitechy AngularJS Tutorial</title>
        <script src="https://ajax.googleapis.com/ajax/libs/angularjs/
        1.5.6/angular.min.js"></script>
    </head> ①
    <body ng-app="">
        <h3>ng-open Directive in AngularJS Tutorial</h3>
        Click Here:<input type="checkbox" ng-model="detail"><br><br>
    ③ <details ng-open="detail"> ②
        <summary>Show the Tutorial List</summary> ④ → ⑤
        <p>HTML</p>
        <p>CSS</p>
        <p>AngularJS</p>
        <p>PHP</p>
    </details>
    </body>
</html>


```

1. The **ng-app** specifies the root element (**<div>**) to define AngularJS application.
2. The **ng-model** bind an input field value to AngularJS application variable (“**detail**”).
3. **<details>** tag is mentioned for the additional information to the user they can view or hide.
4. The **ng-open** directive is used to set the open attribute of a “**detail**”.
5. The **<summary>** tag specifies a visible heading (Show the Tutorial list), which should be clicked to view or hide the details.


Sample Output for ng-open Directive in AngularJS:



1. The output is displayed on page load.



1. If the user clicks the checkbox, then the output shows the details of the text(**Show the Tutorial List**).



2. If the user unclicks the checkbox, then the output hides the details of the text (**Show the Tutorial List**).