

ng-dblclick DIRECTIVE IN ANGULARJS

- **ng-dblclick** directive is used to specify the custom behavior when a HTML element is double-clicked.
- The **ng-dblclick** directive is executing at the priority level is **"0"**
- **ng-dblclick** is supported by all HTML element.
- The **ng-dblclick** directive will not override the element's original ondblclick event, both are executed.

Syntax for ng-dblclick directive in AngularJS:

```
<element ng-dblclick= "expression" > </element>
```

Parameter value for ng-dblclick directive in AngularJS:


| Value | Description |
|------------|--|
| expression | It is used to define an expression that execute when an element is double-clicked. |

Sample coding for ng-dblclick directive in AngularJS:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy AngularJS Tutorials</title>
    <script src="https://ajax.googleapis.com/ajax/libs/
      angularjs/1.5.6/angular.min.js" >
    </script>
  </head>
  <body ng-app="">
    <h2> Wikitechy ng-dblclick Directive in AngularJS </h2>
    <button ng-dblclick="count = count + 1" ng-init="count=0">
      DoubleClick Me!
    </button>
    <h3> The button has been double-clicked : {{ count }} times
  </h3>
  </body>
</html>
```

Code Explanation for ng-dblclick directive in AngularJS:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy AngularJS Tutorials</title>
    1 ← <script src="https://ajax.googleapis.com/ajax/libs/
      angularjs/1.5.6/angular.min.js">
    </script>
  </head>
  <body ng-app="">
    <h2>Wikitechy ng-dblclick Directive in AngularJS </h2>
    <button ng-dblclick="count = count + 1" ng-init="count=0">
      DoubleClick Me!
    </button>
    <h3>The button has been double-clicked : {{count}} times</h3>
  </body>
</html>
```



1. AngularJS is distributed as a JavaScript file, and can be added to a HTML page with a `<script>` tag.
2. The AngularJS application is defined by `ng-app=""`. The application runs inside the `<body>` tag. It's also used to define a `<body>` tag as a root element.
3. The `ng-dblclick="count=count+1"` is used to increase the count variable by one, each time the button is double-clicked.
4. The `ng-init="count = 0"` is used to define the initial value of the count variable is "0".
5. The `{{ count }}` is used to dynamically bind the count variable value when the user double-clicked the button.

Sample Output for ng-dblclick directive in AngularJS:



1. The output displays the **“DoubleClick Me!”** button and content as **“The button has been double-clicked : 0 times”** when the page was loaded.



2. The output shows that the user clicked the **“DoubleClick Me!”** button.
3. The output shows that the **content** changed as **“The button has been double-clicked : 1 times”** when the user double clicked the **“DoubleClick Me!”** button.