

ng-mousedown DIRECTIVE IN ANGULARJS

- **ng-mousedown** directive is used to specify the custom behavior that execute when a mouse button is clicked on the specific HTML element.
- In AngularJS, the **ng-mousedown** directive will not override the HTML element's original **onmousedown** event, both will be executed.
- The **ng-mousedown** directive is compiling at the priority level **"0"** (zero is a default priority level).
- **ng-mousedown** is supported by all HTML elements.

Syntax for ng-mousedown directive in AngularJS:

```
<element ng-mousedown= "expression" > </element>
```

Parameter value for ng-mousedown directive in AngularJS:

Value	Description
expression	It is used to define an expression that execute when a mouse button is clicked.



Sample coding for ng-mousedown directive in AngularJS:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy AngularJS Tutorials</title>
    <script src="https://ajax.googleapis.com/ajax/libs/
      angularjs/1.5.6/angular.min.js">
    </script>
  </head>
  <body ng-app="">
    <h2> ng-mousedown Directive in AngularJS </h2>
    <button ng-mousedown="count = count + 1" ng- init="count=0">
      Click here!
    </button>
    <h3> The mousedown count : {{ count }} </h3>
  </body>
</html>
```



Code Explanation for ng-mousedown directive in AngularJS:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy AngularJS Tutorials</title>
    1 ← <script src="https://ajax.googleapis.com/ajax/libs/
        angularjs/1.5.6/angular.min.js">
    </script>
    2 ← </head>
    <body ng-app="">
      <h2>ng-mousedown Directive in AngularJS</h2>
      3 ← <button ng-mousedown="count = count + 1" ng-init="count=0" >
          Click here!
      </button>
      4 ← <h3>The mousedown count :{{count}} </h3>
      5 ← </body>
    </body>
  </html>
```

1. AngularJS is distributed as a JavaScript file, and can be added to a HTML page with a `<script>` tag.
2. The AngularJS application is defined by `ng-app=""`. The application runs inside the `<body>` tag. It's also used to define a `<body>` tag as a root element.
3. The `ng-mousedown="count=count+1"` is used to increase the count variable by one, every time the mouse button is clicked on the button element.
4. The `ng-init="count = 0"` is used to define the initial value of the count variable is "0".

5. The `{{ count }}` is used to dynamically bind the count variable value when the user clicked the mouse on the button element.

Sample Output for ng-mousedown directive in AngularJS:



1. The output displays that a mouse button clicked on a "Click here!" button.
2. The output shows that the content "**The mousedown count:1**" when the user clicked the mouse button on the "**Click here!**" button. Here the variable "count" will increased a value by 1, every time a mouse button is clicked on the "**Click here!**" button.