

disabled ATTRIBUTE IN HTML

- The **disabled attribute** specifies that the element should be disabled.
- It is a **Boolean attribute**.
- Disabled attribute is **inoperative** and unclickable.
- The disabled attribute is used to keep a user from using the element until some other conditions like selecting a checkbox, etc.,

Syntax for disabled attribute in HTML:

```
<button> disabled</button>
```

Applies to:

Element	Attribute
<button>	disabled
<fieldset>	disabled
<input>	disabled
<keygen>	disabled
<optgroup>	disabled
<option>	disabled
<select>	disabled
<textarea>	disabled

Sample coding:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy-disabled</title>
  </head>
  <body>
    <button type="button" disabled>Wikitechy</button>
  </body>
</html>
```

Code Explanation for disabled attribute in HTML:

```
<!DOCTYPE html>
<html>
  <head>
    <title>Wikitechy-disabled</title>
  </head>
  <body>
    <button type="button" disabled>Wikitechy</button>
  </body>
</html>
```



1. The **disabled attribute** is given to deactivate the button click.

Output of disabled attribute in HTML:



- Here the output displays the disable button, which is shown like unclickable function.

Browser Support for disabled attribute in HTML:

Element	Chrome	IE/Edge	Firefox	Safari	Opera
button	Yes	Yes	Yes	Yes	Yes
fieldset	Yes	Not supported	Yes	7.0	Yes
input	1.0	6.0	1.0	1.0	1.0
keygen	Yes	Not supported	Yes	6.0	Yes
optgroup	1.0	8.0	Yes	Yes	Yes
option	1.0	8.0	1.0	Yes	Yes
select	Yes	Yes	Yes	Yes	Yes
textarea	Yes	Yes	Yes	Yes	Yes

